

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 976 584 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:  
02.02.2000 Bulletin 2000/05

(51) Int Cl.7: B60C 9/06, B60C 15/00

(21) Application number: 99305208.3

(22) Date of filing: 01.07.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: Kuwahara, Takao  
Kita-ku, Kobe-shi, Hyogo-ken (JP)

(74) Representative: Stewart, Charles Geoffrey  
Technical,  
Dunlop Tyres Ltd.,  
Fort Dunlop  
Erdington, Birmingham B24 9QT (GB)

(30) Priority: 02.07.1998 JP 18766198


(71) Applicant: SUMITOMO RUBBER INDUSTRIES  
LTD.  
Hyogo-ken (JP)

(54) Motorcycle tyre

(57) A motorcycle tyre comprises a carcass (6) composed of a low-modulus layer (6L) disposed along the inside of the tyre and a high-modulus layer (6H) disposed outside thereof, the high-modulus layer comprising a high-modulus ply (6a), and the low-modulus layer comprising a low-modulus ply (6b or 6c). Preferably, the cords of each ply are inclined at a bias angle of from 20 to 50 degrees with respect to the tyre equator so that the carcass has a bias structure. The low-modulus layer

(6L) is composed of two low-modulus plies of low-modulus cords extending between bead portions (4) through a tread portion (2) and sidewall portions (3) and turned up around a bead core (5) disposed in each bead portion (4). The high-modulus layer (6H) is composed of a single high-modulus ply of high-modulus cords extending between the sidewall portions through the tread portion and terminated at a position radially outward of the bead cores but radially inward of the maximum width position (M) of the carcass.

Fig.1



## Description

[0001] The present invention relates to a pneumatic tyre for motorcycles, more particularly to an improved carcass structure capable of improving tyre rigidity during cornering and ride comfort during straight running.

[0002] As motorcycles bank during cornering, it is important that motorcycle tyres can display a proper rigidity during cornering to allow the rider to keep a stable bank angle. If the carcass rigidity is increased in order to obtain the necessary tyre rigidity, shock absorption and ride comfort during straight running become worse and further the tyre weight increases. If the carcass rigidity is decreased in order to improve the shock absorbing performance, cornering becomes unstable. Thus, the rigidity during cornering and shock absorption or ride comfort during straight running are antinomy.

[0003] It is therefore an object of the present invention to provide a motorcycle tyre in which both the rigidity during cornering and ride comfort during straight running can be improved.

[0004] According to the present invention, a motorcycle tyre comprises a carcass composed of a low-modulus layer disposed along the inside of the tyre and a high-modulus layer disposed outside thereof, the high-modulus layer comprising at least one high-modulus ply of cords, and the low-modulus layer comprising at least one low-modulus ply of cords.

[0005] The ply modulus is the total of the moduli (initial modulus) of the cords embedded in a unit width (e.g. 5 cm) of the ply as the modulus of rubber is small. Thus the ply modulus can be defined as the product of the modulus of a cord and the cord count per unit width.

[0006] Preferably, the cords of each ply are inclined at a bias angle of from 20 to 50 degrees with respect to the tyre equator so that the carcass has a bias structure.

[0007] The low-modulus layer may be composed of two low-modulus plies of low-modulus cords extending between bead portions through a tread portion and sidewall portions and turned up around a bead core disposed in each bead portion.

[0008] The high-modulus layer may be composed of a single high-modulus ply of high-modulus cords extending between the sidewall portions through the tread portion and terminated at a position radially outward of the bead cores but radially inward of the maximum width position of the carcass.

[0009] In this specification, the high-modulus ply or low-modulus ply means that the ply as a complex of the cords and topping rubber has a relatively high or low modulus.

[0010] An embodiment of the present invention will now be described in detail in conjunction with the accompanying drawing:

Fig.1 is a cross sectional view of an embodiment of the present invention.

[0011] A motorcycle tyre according to the present invention comprises a tread portion 2, a pair of sidewall portions 3, a pair of bead portions 4 each with a bead core 5 therein, and a carcass 6 extending between the bead portions 4.

[0012] In the tread portion 2, no belt or breaker as a tread reinforcing layer is provided. The tread is curved by a relatively small radius of curvature compared to other vehicle tyres so that the maximum tyre width TW lies between the tread edges E.

[0013] In this embodiment, the tyre is adapted for off-road use, and the tread portion 2 is provided with a block pattern made up of a plurality of blocks B each having a dent to improve road grip.

[0014] Each of the bead portions 4 is provided with a bead apex 8 made of hard rubber extending radially outwards from the bead core 5. The Shore A hardness thereof is in a range of 65 to 95 for example.

[0015] The above-mentioned carcass 6 is composed of a low-modulus layer 6L disposed along the inside of the tyre and a high-modulus layer 6H disposed on the outside of the low-modulus layer 6L.

[0016] The high-modulus layer 6H comprises a high-modulus ply 6a, and the low-modulus layer 6L comprises two low-modulus plies 6b and 6c.

[0017] Each of the plies 6a, 6b and 6c is made of rubberised cords arranged at a bias angle in the range of from 20 to 50 degrees (in this example 28 to 35 degrees) with respect to the tyre equator C. In a relationship between the adjacent plies, the cords in one ply cross the cords in the other ply. Accordingly, the carcass 6 has a bias structure. Therefore, the tread portion 2 can display a good enveloping effect, and ride comfort and off-road grip can be improved.

[0018] Each of the low-modulus plies 6b and 6c extends between the bead portions 4 through the tread portion 2 and sidewall portions 3 and is turned up around each bead core 5 from the inside to the outside of the tyre to be secured thereto.

[0019] For the low-modulus cords or the cords of the low-modulus plies, those having an initial modulus of less than 6000 N/sq.mm are preferably used. In this example, nylon cords (2/940 dtex, 2/1400 dtex) having an initial modulus of about 5500 to 5900 N/sq.mm are used.

[0020] The height h2 of the turnup portion of the low-modulus outer ply 6b is in the range of from 0.3 to 0.4 times the tyre section height H. The height h3 of the turnup portion of the low-modulus inner ply 6c is in the range of from 0.45 to 0.6 times the tyre section height H. The heights are measured from the bead base line BL.

[0021] The above-mentioned high-modulus ply 6a extends between the sidewall portions 3 through the tread portion 2. The edges or ends thereof are positioned radially outward of the bead cores 5 but radially inward of the maximum width position M of the carcass 6. Thus, this ply 6a is not turned up in the bead portions 4.

[0022] The high-modulus ply 6a is made of high-modulus cords having a modulus higher than the above-mentioned low-modulus cords.

[0023] For the high-modulus cords, organic fibre cords having an initial modulus of not less than 7000 N/sq.mm, preferably not less than 7500 N/sq.mm are used. In this example, polyester cords (2/1670 dtex) having an initial modulus of about 7500 to 7600 N/sq.mm and aramid cords (2/1670 dtex) having an initial modulus of about 8500 to 8700 N/sq.mm are used. Also, a hybrid cord of two or more materials can be used.

[0024] Therefore, the sidewall portions 3 are reinforced and the lateral stiffness providing rigidity during cornering is increased. If the high-modulus layer 6H does not exist around the maximum width position M, the rigidity is insufficient. If the high-modulus layer 6H reaches to the bead cores, when the tyre is mounted on a wheel rim, the radially inner ends are firmly secured to the bead cores by a large compressive force from the rim flanges. Thus, it functions like a turned-up ply, and the ride comfort greatly deteriorates.

[0025] The radially inner edges of the high-modulus ply 6a are disposed axially inside the turnup portion 6A of the low-modulus ply so that the ends are covered by the low-modulus ply.

[0026] In this embodiment, further, the above-mentioned bead apexes 8 are extended to the edges of the high-modulus ply 6a. Furthermore, each of the bead portions 4 is provided with a bead reinforcing layer 9 extending along the axially inner surface and outer surface of the bead portion 4 to increase the bead rigidity. In this example, the bead reinforcing layer 9 is composed of one ply of organic fibre cords, e.g. nylon, polyester, rayon, aromatic polyamide and the like embedded in rubber in parallel formation. Preferably, the height h4 of the axially outer part of the bead reinforcing layer 9 measured from the bead base line BL to the radially outer end thereof is set in the range of from 0.1 to 0.25 times the tyre section height H.

[0027] As a result, the rigidity is gradually decreased from the bead core 5 to the neighbourhood of the tread edge E. And it becomes possible to show a suitable rigidity according to the camber angle during cornering. Further, ply separation failures can be prevented.

[0028] The modulus of ply is defined as the total modulus of the cords plus the modulus of topping rubber per a unit width of the ply. In this embodiment, as the high-modulus ply is made of high-modulus cords and the low-modulus ply is made of low-modulus cords, the high-modulus ply is higher in modulus than the low-modulus ply. However, it is possible that the high-modulus ply 6a is made of cords identical with those of the low-modulus ply 6b, 6c. In this case, however, in order to increase the ply modulus, the cord count or density of the high-modulus ply 6a must be higher than each of the low-modulus plies 6b and 6c.

[0029] When the low-modulus layer 6L and/or the high-modulus layer 6H are composed of a plurality of plies, the modulus of ply can be changed from one another in each layer. In this case, it is preferable that the inner the ply location is, the lower the ply modulus is.

#### Comparison Test:

[0030] Test tyres having the same structure shown in Fig.1 except for the carcass structure were made and tested for rigidity during cornering, ride comfort and shock absorption at the time of landing subsequent to a high jump. These performances were evaluated by a test rider's feelings while running a motocross bike on a test course. The results are indicated in Table 1 by an index based on reference tyre 1 being 100.

[0031] From the test results, it was confirmed that Example tyres according to the present invention were improved in both the rigidity during cornering and ride comfort during straight running.

Table 1

Tyre	Ref.1	Ref.2	Ref.3	Ref.4	Ex.1	Ex.2	Ref.5	Ref.6	Ref.7	Ref.8	Ex.3	Ex.4
Tyre size**	80	80	80	80	80	80	110	110	110	110	110	110

\*1) 80: 80/100-21 51M K490  
110: 110/90-19 62M D737

# EP 0 976 584 A2

Table 1 (continued)

Tyre	Ref.1	Ref.2	Ref.3	Ref.4	Ex.1	Ex.2	Ref.5	Ref.6	Ref.7	Ref.8	Ex.3	Ex.4
High-modulus layer* <sup>2</sup>	PE	PE	NY	NY	PE	PE	PE	PE	NY	NY	PE	PE
cord material* <sup>4</sup>												
cord angle (deg.)	31	31	31	31	31	31	31	31	31	31	31	31
h1/H	0.23	0.23	0.23	0.23	0.23	0.23	0.23	0.23	0.23	0.23	0.23	0.23
Low-modulus layer* <sup>3</sup>	PE	PE	PE	NY	NY	NY	PE	PE	PE	NY	NY	NY
cord material* <sup>4</sup>												
cord angle (deg.)	31	31	31	31	31	31	31	31	31	31	31	31
h2/H	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35
h3/H	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.52	0.52
h4/H	0.17	0.13	0.17	0.17	0.17	0.13	0.17	0.13	0.17	0.17	0.17	0.13
Tyre weight (kg)	3.9	3.8	3.85	3.65	3.7	3.6	5.7	5.6	5.65	5.35	5.4	5.3
Rigidity	100	80	95	80	100	100	100	80	95	80	100	100
Shock absorption	100	105	105	110	120	110	100	105	105	90	120	110
Ride comfort	100	110	105	110	110	120	100	110	105	110	110	120

\*2) Single ply (not turned up)

\*3) Two plies (turned up)

\*4) PE: 2/1670 dtex polyester cord  
NY: 2/940 dtex nylon cord

## Claims

1. A motorcycle tyre comprising a carcass (6), characterised in that it is composed of a low-modulus layer (6L) disposed along the inside of the tyre and a high-modulus layer (6H) disposed outside thereof, said high-modulus layer (6H) comprising at least one high-modulus ply (6a) of cords, said low-modulus layer comprising at least one low-modulus ply (6b or 6c) of cords, said at least one high-modulus ply (6H) being higher in modulus than said at least one low-modulus ply (6L).
2. A motorcycle tyre according to claim 1, characterised in that said cords of each of said at least one high-modulus ply (6a) and said at least one low-modulus ply (6b or 6c) are inclined at a bias angle of from 20 to 50 degrees with respect to the tyre equator so that the carcass has a bias structure, said at least one low-modulus ply (6L) comprises two plies (6b, 6c) of low-modulus cords extending between bead portions (4) through a tread portion (2) and sidewall portions (3) and turned up around a bead core disposed in each bead portion (4), and said at least one high-modulus ply (6H) is a single ply (6c) of high-modulus cords extending between the sidewall portions (3) through the tread portion (2) and terminated at a position radially outward of the bead cores (5) but radially inward of the maximum width position (M) of the carcass.
3. A motorcycle tyre according to claim 1 or 2, characterised in that said high-modulus cords are a polyester cord, and said low-modulus cords are nylon cords.
4. A motorcycle tyre according to any of claims 1 to 3, characterised in that the low modulus ply (6L) comprises cords having an initial modulus of less than 6000 N/sq.mm.
5. A motorcycle tyre according to claim 4, characterised in that the high modulus ply (6H) comprises cords having

**EP 0 976 584 A2**

an initial modulus not less than 7000 N/sq.mm.

5

10

15

20

25

30


35


40

45

50

55





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 976 584 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
23.01.2002 Bulletin 2002/04

(51) Int Cl.7: B60C 9/06, B60C 15/00

(43) Date of publication A2:  
02.02.2000 Bulletin 2000/05

(21) Application number: 99305208.3

(22) Date of filing: 01.07.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(71) Applicant: Sumitomo Rubber Industries Ltd.  
Kobe-shi, Hyogo-ken (JP)

(72) Inventor: Kuwahara, Takao  
Kita-ku, Kobe-shi, Hyogo-ken (JP)

(30) Priority: 02.07.1998 JP 18766198


(74) Representative: Stewart, Charles Geoffrey  
Technical, Dunlop Tyres Ltd., Fort Dunlop  
Erdington, Birmingham B24 9QT (GB)

(54) Motorcycle tyre

(57) A motorcycle tyre comprises a carcass (6) composed of a low-modulus layer (6L) disposed along the inside of the tyre and a high-modulus layer (6H) disposed outside thereof, the high-modulus layer comprising a high-modulus ply (6a), and the low-modulus layer comprising a low-modulus ply (6b or 6c). Preferably, the cords of each ply are inclined at a bias angle of from 20 to 50 degrees with respect to the tyre equator so that the carcass has a bias structure. The low-modulus layer

(6L) is composed of two low-modulus plies of low-modulus cords extending between bead portions (4) through a tread portion (2) and sidewall portions (3) and turned up around a bead core (5) disposed in each bead portion (4). The high-modulus layer (6H) is composed of a single high-modulus ply of high-modulus cords extending between the sidewall portions through the tread portion and terminated at a position radially outward of the bead cores but radially inward of the maximum width position (M) of the carcass.

Fig.1



EP 0 976 584 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 30 5208

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 3 980 119 A (NAKASAKI EIJI) 14 September 1976 (1976-09-14) * column 2, line 21 - column 3, line 2 * * claims 1,2 * * figure 1 *	1,2	B60C9/06 B60C15/00
X	EP 0 835 766 A (SUMITOMO RUBBER IND) 15 April 1998 (1998-04-15) * column 2, line 10 - line 29 * * claims 4,5; figure *	1,4,5	
X	US 4 770 222 A (MEZZANOTTE MARIO) 13 September 1988 (1988-09-13) * column 3, line 10 - line 58 * * column 5, line 1 - line 11 * * figures *	1	
E	EP 0 928 703 A (PIRELLI) 14 July 1999 (1999-07-14) * paragraphs '0078!', '0079!'; figure 2 *	1,4,5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B60C
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 27 November 2001	Examiner Pesche], W
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention I : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (03.02) (P.04001)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 5208

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

27-11-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 3980119	A	14-09-1976	BE 818106 A1	27-01-1975
			CA 1012046 A1	14-06-1977
			DE 2435935 A1	13-02-1975
			DK 403774 A	10-03-1975
			FR 2238601 A1	21-02-1975
			GB 1438922 A	09-06-1976
			LU 70618 A1	21-05-1975
			NL 7410144 A	28-01-1975
EP 0835766	A	15-04-1998	EP 0835766 A2	15-04-1998
			JP 10114203 A	06-05-1998
US 4770222	A	13-09-1988	IT 1163837 B	08-04-1987
			AT 41626 T	15-04-1989
			AU 565685 B2	24-09-1987
			AU 3076184 A	24-01-1985
			BR 8403685 A	26-12-1984
			CA 1221009 A1	28-04-1987
			DE 3477360 D1	27-04-1989
			EP 0133255 A2	20-02-1985
			ES 280834 U	16-02-1985
			GR 82204 A1	13-12-1984
			JP 4041082 B	07-07-1992
			JP 60053403 A	27-03-1985
			TR 23526 A	01-03-1990
			ZA 8405417 A	27-03-1985
EP 0928703	A	14-07-1999	EP 0928703 A1	14-07-1999
			BR 9805816 A	14-12-1999
			JP 11245616 A	14-09-1999
			TR 9802736 A1	21-07-1999

EPO FORM 100/99

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

